

# Environment Variables

**ROOT\_URL:** the URL under which titra is served. Could be `http://localhost:3000` for a local instance or `https://app.titra.io` for a setup with reverse proxy and DNS records.

**MONGO\_URL:** the URL of the mongoDB backend (e.g. `mongodb://localhost:27017/titra`)

**MONGO\_OPLOG\_URL:** the URL pointing to the OPLOG of the mongoDB backend (e.g. `mongodb://localhost:27017/local`)

**MAIL\_URL:** The server reads from the `MAIL_URL` environment variable to determine how to send mail. The `MAIL_URL` should reference an [SMTP](#) server and use the form:

```
smtp://USERNAME:PASSWORD@HOST:PORT
```

or

```
smtps://USERNAME:PASSWORD@HOST:PORT
```

The `smtps://` form (the **s** is for “**secure**”) should be used if the **mail server requires TLS/SSL** (and does not use STARTTLS) and is most common on port 465. Connections which start unencrypted prior to being upgraded to TLS/SSL (using STARTTLS) typically use port 587 (and sometimes 25) and should use `smtp://`. For more information see the [Nodemailer](#) docs

## METEOR\_SETTINGS are Deprecated starting with titra version 0.18.0

Please use the new Globalsettings available for administrators through the Administration page.

**METEOR\_SETTINGS:** the titra specific settings in JSON format, all settings have to belong to the “public” hierarchy. The available parameters are:

`disablePublic:` true/false – if set to true, projects can not be set as public

enableAnonymousLogins: true/false – if set to true, the /try path will be available allowing anonymous accounts to be created on the fly.

Below is an example for a METEOR\_SETTINGS environment variable value:

```
{
  "public": {
    "disablePublic": "true",
    "enableAnonymousLogins": "true"
  }
}
```

---

Revision #3

Created 2021-07-30 06:38:59 UTC

Updated 2023-03-07 08:56:18 UTC by titra team